



AEON®

TINTED PRIMER WHITE



DATA SHEET

CODE: FT-109-ENG

LEVEL REVIEW: 03

REVIEW DATE: NOV/2016

ELEMENT OF THE STANDARD: 7

• GROUP SEALERS WATER BASE

• PRODUCT NAME AEON TINTED PRIMER WHITE

• CHARACTERISTICS

Aeon Tinted Primer white is a Sealer made from modified acrylic emulsion and raw materials of the highest quality, materials containing no lead or mercury, zero emissions of solvents. It is also easy to apply.

• USES AND PROPERTIES

The acrylic sealant can be used in interior and exterior, necessary in the treatment of cement surfaces, plasterboard or any type of flattening prior to the application of the desired final coating. The use of the matte sealer blocks the porosity of the substrate by helping to obtain a higher yield of the final coating by increasing the life of the finish. Recommended for previously treated surfaces requiring maintenance or repainting. It is ideal for receiving water-based finishes in intense colors.

• SURFACE PREPARATION

General conditions, the surface should be dry, clean, free of dust, grease, poorly adhered films or any foreign particles. If necessary, repair any imperfection or failure of the substrate before applying the sealant, removal of old paint by sanding, scraping or other means. Glossy surface should be sanded dull.

• APPLICATION

DILUTION: It is recommended to dilute the product with clean water up to 15% vol. On substrates that have previous paints or enamel, it will be necessary to perform an adhesion test to determine if it is possible to

repaint or it will be necessary to remove old or deteriorated paint. In the case of enamels, the surface must be sanded or brushed (with a bristle brush) to completely eliminate the gloss of the previous film, to prevent the sealant from losing its adhesion. Once the above is done, clean the surface to remove loose particles and dust, apply sealant using brush, brush, roller or sprinkler, allow to dry completely before applying the finish.

• CLEAN UP INFORMATION

Clean spills, splatters, hands and tools immediately after use

With soap and warm water. After cleaning flush spray equipment with a compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.

• CAUTION

Protect from freezing

Store in a cool, covered place at a temperature not less than 41 °F or greater than 95 °F.

Avoid contact with eyes and skin, wash hands, after using. Keep container closed when not in use.

First Aid in case of eye contact, flush thoroughly with large amounts of water, gets medical attention if irritation persists.

DO NOT TAKE INTERNALLY, KEEP OUT OF THE REACH OF CHILDREN.

WARNING: ITP, S.A. de C.V. guarantees that all information presented are true which in case of any failure of this product which causes any damage will be responded to immediately. All instructions must be followed exactly to insure the guarantee of this product.

ITP guarantees this product against all defects in manufacturing.

TECHNICAL DATA

VEHICLE TYPE	STYRENE-ACRYLIC
VISCOSITY STORMER (U.KREBS)	_____108-112
WEIGHT PER GALON (LB/GAL.)	_____11.56 ± 0.58
WEIGHT SOLIDS (%)	_____50 ± 2
VOLUME SOLIDS (%)	_____30 +/- 2
PH	_____8 - 9.5
DRYING TIME TO TOUCH (MINUTES)	_____30 Average
COVERAGE PER GALLON (Sq. Ft.)	_____326 - 408 (one coat)